

WEB'LOG PRO

Article nos.: 421.145, 421.146,
421.147, 421.148



AMBIENT TEMPERATURE

Operating temperature:	0°C to 55°C
Storage and transport:	-20°C to 65°C
Protection class:	IP 20

TECHNICAL DATA

Power supply:	AC: 230 V (85 V to 240 V, 47 Hz to 63 Hz) or DC: 24 V
Analog inputs (configurable):	Quantity: 4 Voltage measurement (DC): 0 V to 10 V (max. 24 V) Current measurement (DC): 0 mA to 20 mA (max. 40 mA/3 V) Resistance measurement: PT1000
Digital inputs (configurable):	Quantity: 4 Pulse input according to DIN 43864 (S0) DC: low = 0 V to 7 V, high = 9 V to 24 V (function only through the unit's power supply) Status input
Digital output:	Quantity: 1 Optocoupler output according to DIN 43864 (S0) Max. load (DC): 70 V/50 mA (use correct polarity!) Alarm output or pulse output
Power consumption:	AC: max. 9 W at 230 V (in measurement mode without sensors) Max. current for sensors and i'checker: 100 mA DC: max. 3.5 W at 24 V (in measurement mode without sensors)

DISPLAY	192x32 dot display 4 LEDs
----------------	------------------------------

INTERFACES

Modem (optional):	PSTN modem (analog) ISDN modem GSM/GPRS modem (quad-band modem for 900/1800/850/1900 MHz)
Network:	Ethernet connection (100 Mbit/s)
Communication:	1 x RS485 1 x RS422

MEASUREMENT IMPRECISION

Voltage input: 1% of the final value (0.1 V)
Current input: 1% of the final value (0.2 mA)

STORAGE MEDIUM

CF card

BATTERY

Lithium cell / type: Li2032 time buffering

MECHANICAL DATA

Dimensions: 160 mm x 110 mm x 63 mm (WxHxD)
Installation: Top-hat rail or wall mounting
Weight: 436 g

meteocontrol GmbH | Spicherer Strasse 48 | 86157 Augsburg | Germany | Telephone +49 (0)821 34666-0 | Fax +49 (0)821 34666-11
E-mail info@meteocontrol.com | Web www.meteocontrol.com